

SECTION 1.2 2 1/2" (64.5 mm) CURTAIN WALL INDEX

SECTION 1.2.1	2500 SERIES PRIMARY COMPONENTS PAGES	1.2.1.1 TO 1.2.1.5
SECTION 1.2.2	TYPICAL DETAILS OF CAPPED SYSTEM	1.2.2.0 TO 1.2.2.10
SECTION 1.2.3	TYPICAL DETAILS OF SSG SYSTEM	1.2.3.0 TO 1.2.3.7
SECTION 1.2.4	TYPICAL DETAILS OF PRE-FAB, PRE-GLAZE SYSTEM	1.2.4.1 TO 1.2.4.4
SECTION 1.2.5	2500e THERMALLY ENHANCED CURTAIN WALL	1.2.5.1 TO 1.2.5.4
SECTION 1.2.6	HIGH SPAN CURTAIN WALL	1.2.6.1 TO 1.2.6.2
SECTION 1.2.7	ANCHORS AND ANCHORING	1.2.7.1 TO 1.2.7.3
SECTION 1.2.8	MISCELLANEOUS DETAILS	1.2.8.1 TO 1.2.8.1
SECTION 1.2.9	WIND LOAD CHARTS - CAPPED SYSTEM	1.2.9.1 TO 1.2.9.11
SECTION 1.2.10	WIND LOAD CHARTS - SSG SYSTEM	1.2.10.1 TO 1.2.10.8
SECTION 1.2.11	DEAD LOAD CHARTS	1.2.11.1 TO 1.2.11.10
SECTION 1.2.12	TOTAL SYSTEM COMPONENTS	1.2.12.1 TO 1.2.12.18
SECTION 1.2.13	SPECIFICATIONS	1.2.13.1 TO 1.2.13.3

OUR MOST COMPREHENSIVE AND VERSATILE CURTAIN WALL SYSTEM IN A 2 1/2" (63.5 mm) PROFILE. WHETHER THE PROJECT REQUIREMENTS ARE BEST SUITED TO A STICK SYSTEM, A PRE-FABRICATED SYSTEM OR PRE-GLAZED SYSTEM, 2500 SERIES IS SUITABLE FOR ALL OF THESE APPLICATIONS.

CONVENTIONAL CAPPED, TWO SIDED STRUCTURAL SILICONE GLAZING AS WELL AS **FOUR SIDED SSG** OPTIONS ARE AVAILABLE AND FOR ENHANCED THERMAL PERFORMANCE **2500e** WILL MEET STRINGENT REQUIREMENTS AT A FRACTION OF THE COST OF THE COMPETITION. **2500 HIGH SPAN** SECTIONS CAN ATTAIN UNSUPPORTED HEIGHTS OF 24 ft (7.3 M) AND GREATER. A WIDE VARIETY OF SQUARE, EXTENDED, ROUND AND SHAPED EXTERIOR CAPS ARE AVAILABLE OR CAN BE CUSTOM DESIGNED TO SUIT PROJECT NEEDS AND ANY ALUMICOR OPERABLE WINDOW PRODUCT MAY BE EASILY INCORPORATED INTO THE SYSTEM.