

# SECTION 1.5 2" (50.0 mm) CURTAIN WALL INDEX

SECTION 1.5.1	<b>2200 SERIES</b> PRIMARY COMPONENTS PAGES	1.5.1.1 TO 1.5.1.2
SECTION 1.5.2	TYPICAL DETAILS	1.5.2.0 TO 1.5.2.9
SECTION 1.5.3	2200 SERIES RIBBON WINDOW	1.5.3.1 TO 1.5.3.4
SECTION 1.5.4	<i>RESERVED FOR FUTURE USE</i>	
SECTION 1.5.5	<i>RESERVED FOR FUTURE USE</i>	
SECTION 1.5.6	<i>RESERVED FOR FUTURE USE</i>	
SECTION 1.5.7	WIND LOAD CHARTS	1.5.7.1 TO 1.5.7.6
SECTION 1.5.8	DEAD LOAD CHARTS	1.5.8.1 TO 1.5.8.6
SECTION 1.5.9	TOTAL SYSTEM COMPONENTS	1.5.9.1 TO 1.5.9.9
SECTION 1.5.10	SPECIFICATIONS	1.5.10.1 TO 1.5.10.3

A SLIGHTLY LIGHTER PROFILE THAN THE 2500 SERIES AT 2" (50 mm) NOMINAL, THE 2200 SERIES CURTAIN WALL IS IDEAL FOR LOW TO MEDIUM RISE CURTAIN WALL APPLICATIONS AS WELL AS FOR STOREFRONT. IT IS ALSO AVAILABLE AS A SPLIT MULLION RIBBON WINDOW SYSTEM WITH TWO SIDED SSG OPTION AND A UNIQUE AND CONVENIENT PERIMETER ANCHORING DESIGN.

NOTES:

---

---

---

---

---