

SECTION 5.2 NON-THERMALLY BROKEN STOREFRONTS INDEX

SECTION 5.2.1	800 SERIES PRIMARY COMPONENTS PAGE	5.2.1.1 TO 5.2.1.1
SECTION 5.2.2	TYPICAL DETAILS OF 800 SERIES	5.2.2.1 TO 5.2.2.10
SECTION 5.2.3	WIND LOAD CHARTS	5.2.3.1 TO 5.2.3.2
SECTION 5.2.4	DEAD LOAD CHARTS	5.2.4.1 TO 5.2.4.4
SECTION 5.2.5	TOTAL SYSTEM COMPONENTS	5.2.5.1 TO 5.2.5.4
SECTION 5.2.6	<i>RESERVED FOR FUTURE USE</i>	
SECTION 5.2.7	1800 SERIES PRIMARY COMPONENTS PAGE	5.2.7.1 TO 5.2.7.1
SECTION 5.2.8	TYPICAL DETAILS OF 1800 SERIES	5.2.8.1 TO 5.2.8.7
SECTION 5.2.9	WINDLOAD CHARTS	5.2.9.1 TO 5.2.9.2
SECTION 5.2.10	DEAD LOAD CHARTS	5.2.10.1 TO 5.2.10.4
SECTION 5.2.11	TOTAL SYSTEM COMPONENTS	5.2.11.1 TO 5.2.11.5
SECTION 5.2.12	<i>RESERVED FOR FUTURE USE</i>	
SECTION 5.2.13	500 SERIES PRIMARY COMPONENTS PAGE	5.2.13.1 TO 5.2.13.1
SECTION 5.2.14	TYPICAL DETAILS OF 500 SERIES	5.2.14.1 TO 5.2.14.10
SECTION 5.2.15	TOTAL SYSTEM COMPONENTS 500 SERIES	5.2.15.1 TO 5.2.15.4
SECTION 5.2.16	SPECIFICATIONS	5.2.16.1 TO 5.2.16.3

FROM THE HIGH PERFORMANCE, THERMALLY BROKEN 3400 SERIES WITH "BIGFOOT" THERMAL BREAK TECHNOLOGY TO OUR SIMPLE AND ECONOMICAL 500 SERIES FIN TUBE, ALUMICOR HAS A STOREFRONT FOR VIRTUALLY ANY APPLICATION. FOR INNOVATIONS SPECIFIC TO YOUR PROJECT CONTACT YOUR ALUMICOR REPRESENTATIVE